Page 1 of 9

006366323 [file://C:\WINDOWS\TEMP\006366323 cpc]

(12) United States Patent Shono US006366323B1
(10) Patent No.: US 6,366,323 BL

(45) Date of Patent:

Apr. 2, 2002

		x (X)					
(54)	DIGITAL CAMERA WITH MOVEABLE IMAGE PICKUP DEVICE						
(75)	inventor:	Tetsuji Shono, Saitama-ken (JP)					
(73)	Assignee:	Asuhi Kogaku Kogyo Kabushiki Kalshu, Tokyo (IP)					
(*)	Notice:	Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days					
(21)	) Appl No : 09/089,404						
(22)	Filed:	Jun. 3, 1998					
(30) Foreign Application Priority Data							
Jun	12, 1997	(JP)					
(51) Int. Cl. <sup>7</sup>							
(52)	U.S. Cl. 348/340; 348/335; 348/373; 348/374; 396/75; 396/270; 396/349						
(58) Field of Senrch 348/335, 340, 348/360, 361, 373, 374; H04N 5/232							
(56)	•	References Ched					
US PATENT DOCUMENTS							
	4,803,557 A 4,961,115 A 5,557,327 A 5,706,051 A 6,031,998 A	* 10/1990 Jessop					

FOREIGN PATENT DOCUMENTS
000549300 A1 • 6/1993

... H04N/5/232

111	406230263 A	• 8/1094		G02B/7/U4 -
IP.	406303497 A			H04N/5/232
IP.	08009230 A			H04N/5/232
IP.	008126759 A	_,		H04N/5/232
ΙP	008237529 A	- 9/1996	·	HO4N/5/232
		•		

cited by examiner

Primary Examiner—Wendy R Garber Assistant Examiner—John M Villecco (74) Atturney, Agent, or Firm—Greenblum & Bernstein, P.L.C

## (57) ABSTRACT

A digital camera which includes: a photographic lens movable along an optical axis thereof between a retracted position and a photographing position in front of the retracted position; an image pick-up device on which an object image is formed through the photographic lens, the image pick-up device being guided to be movable between a first position where the image pick-up device is positioned in a photographic optical path of the photographic lens behind the photographic lens and a second position where the image pick-up device is positioned out of the photographic optical path; and a mechanism for moving the image pick-up device between the first position and the second position, wherein the moving mechanism moves the image pick-up device to the first position to the photographing position, and wherein the moving mechanism moves the image pick-up device to the second position when the photographing position, and wherein the moving mechanism moves the image pick-up device to the second position when the photographic lens is moved from the photographing position to the retracted position

13 Claims, 3 Drawing Sheets

